► print ► copy ► scan ► fax

A3 COLOUR MULTIFUNCTIONAL

LET COLOUR WORK FOR YOU.

high-quality colour output and high productivity at the same time. Reliable and easy to use, it can carry out one job while another is in progress, ensuring deadlines are met. Offering a wide range of clever options, this device can be tailored to the specific needs of any office.

- 25 pages per minute monochrome printing and copying,
 25 pages per minute colour printing and copying
- Standard duplex printing
- Standard network printing and scanning in colour
- 768 MB copy memory standard, 40 GB HDD
- 256 MB printer memory standard, upgradeable to 1 GB
- · Long-life components for outstanding reliability

Product depicted includes optional extras

Area Separation Processing treats text and photos in different ways, delivering optimum copy and scan results.



The KM-C2525E can be upgraded with a 1,000-sheet finisher, to give your work that professional edge.







KM-C2525E

A3 COLOUR MULTIFUNCTIONAL

The KM-C2525E incorporates extremely durable components that quarantee efficient and reliable operation to meet the demanding requirements of busy office environments. The KM-C2525E provides effective productivity and maximises uptime whilst ensuring a minimum impact on the environment.

Technology: Kyocera Laser Colour **Engine speed:** Max. 25/13 pages per minute A4/A3 in b/w mode, max. 25/13 pages per minute A4/A3 in full colour mode Resolution: 600 x 600 dpi multi bit technology

Time to first copy: 5.9 seconds or less in b/w, 7.9 seconds or less in colour

Warm-up time: 45 seconds or less Power Source: AC 220 V ~ 240 V, 50/60 Hz

Power Consumption: Printing: 700 W, Stand-By: 270 W, Power-Saving (ECOpower): 16 W Noise (ISO 7779): Printing: 65.5 dB(A), Stand-By: 53.3 dB(A)

Power-Saving (ECOpower): Immeasurably low

Dimensions (W x D x H): Main unit: 605 x 660 x 745 mm

Weight: Main unit: Approx. 98 kg

Certification: TÜV/GS, CE, PTS
This product is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera under normal environmental conditions.

Input capacity: 2 x 500-sheet universal paper cassette, 60-105 g/m^2 , A3-A5R, Letter, Legal, Custom (over A4 size up to 250 sheets)

100-sheet multi-purpose tray, 60-220g/m², A3-A6R, Folio,

envelopes Max, input capacity with options: 4,100 sheets Duplex as standard supports A3-A5, 60-105 g/m² Output capacity: 250 sheets

Max. original size: A3

Continuous copying: 1-999 Memory capacity: Standard 768 MB (max. 768 MB) + 40 GB HDD

Zoom range: 25-400% in 1% steps Preset magnification ratios: 5R / 5E

Digital features: Auto colour selection, auto cassette change. auto paper selection, auto magnification selection, energy save mode, interrupt copy, scan-once-print-many, electronic sort, rotate copy, booklet copy, N-up copy, page numbering. cover mode, invert, mirror, poster mode, border erase,
OHP mode, image repeat copy
Exposure mode: Auto, manual: 7 or 13 steps

Image adjustments: Text, Mixed, Print, Photo, Map colour balance adjustment, hue adjustment, one-touch colour adjustment

Your Kyocera Business Partner:

Processor: PowerPC 750FL / 600MHz Memory: Standard 256 MB (max. 1 GB) + 40 GB HDD (HD-5) Emulations: PCL 6/PCL 5e/PCL 5c, KPDL3 (PostScript 3

compatible), KC-GL (HP-GL7550A)

Controller language: PRESCRIBE IIc

Fonts: 80 outline fonts (PCL6), 136 outline fonts (KPDL3),

1 bitmap font, 45 types of one-dimensional barcodes, plus two-dimensional barcode PDF-417 **Print features:** eMPS – for quick copy, proof and hold, private print, PDF direct printing

Interfaces

Standard interface: High speed bi-directional parallel (IEEE 1284), USB 2.0 (Hi-Speed), Fast Ethernet 10/100Base-TX, 2 KUIO-LV slots

Multiple interface connection (MIC): Allows simultaneous data transfer via up to four interfaces, with each interface having its own virtual printer.

Functionality: Scan-to-PC, scan-to-email, scan-to-FTP

network TWAIN, scan-to-SMB

Scan speed: 32 originals per minute (600 dpi/A4) Scan resolution: 600, 400, 300, 200 dpi (256 grayscales)

Original recognition: Text, photo, text + photo, OCR

Interface: 10/100Base-TX Network protocol: TCP/IF File types: Colour: PDF, JPEG, TIFF

Mono: PDF, TIFF

Compression format: TIFF (MMR), colour: JPEG Features: High compression PDF, Encrypted PDF

Bundled software: DB-Assistant, Scanner file utility, Address book, Address editor, TWAIN Source, PaperPort Deluxe 9.0

Applicable OS: Windows® 95, 98, Me, NT4.0, 2000, XP, Vista, Server 2003

Compatibility: ITU-T Super G3 Modem speed: Max. 33.6 kbps

Transmission speed: 2 seconds or less (JBIG)

Scanning speed: 1 second
Scanning density: Normal: 8 dot/mm x 3.85 line/mm, Fine: 8 dot/mm x 7.7 line/mm, Superfine: 8 dot/mm x 15.4 line/mm, Ultrafine: 16 dot/mm x 15.4 line/mm (with optional memory), halftone

Max. original size: A3

Compression method: JBIG, MMR, MR, MH Memory: Standard 4 MB, max. 32 MB

Features: Network faxing, rotate transmission, duplex fax reception, N-up reception, mailbox, remote diagnostics

Fax system (N)

Paper handling

2-710 Document processor: Reversing document processor, 100 sheets, 35-160 g/m², A3-A5R, Folio (ADF) 100 sheets, 50-120 g/m², A3-A5R, Folio (RADF) PF-710 Paper feeder: 2 x 500 sheets, 60-105 g/m², A3-A5R, Fo PF-750 Paper feeder: Max. 3,000 sheets, 60-105 g/m², A4,

R5 Letter DF-710 Document finisher + AK-710* + JS-710**

Main tray: Max. 3.000 sheets A4 or 1.500 sheets A3

face-down, 60-105 g/m², A3-B5, Sub tray left: Max. 200 sheets A4 or 100 sheets A3/B4 face-up, 60-105g/m2, A3-A6R,

Sub tray right: Max. 50 sheets A4 face-up, 60-105 g/m², A4-A6R,

Stapling: Max. 50 sheets A4 or 30 sheets A3, stapling at 3 positions

DF-730 Document finisher + JS-710**: Max. 1,000 sheets A4 or 500 sheets A3/B4, 60-105 g/m², A3-B5, one position stapling max. 30 sheets A4 or 20 sheets A3/B4, 60-105 g/m² **PH-5C Punch unit for DF-710**: A3-A5R, 60-105 g/m², 2-hole/4-hole

MT-710 Mailbox for DF-710: 7 bins, 60-80 g/m², A3-A5R, 7 bins x 100 sheets A4 or 50 sheets A3/B4 **BF-710 Booklet unit for DF-710:** Max. 64 pages (16 sheets)

booklet folding and stapling, 60-80 g/m², cover sheet 60-105 g/m², A3, B4, A4R

JS-710 Job separater**: 100 sheets internal job separator,

60-105 g/m², A3-A5R

*Adapter-Kit AK-710 is required for the use of DF-710

document finisher.
**JS-710 is required for the use of DF-710/DF-730 document finisher.

The use of the hard disk HD-5 or extended RAM-Disk size is highly recommended to achieve full document finisher functionality.

Printer Memory

DIMM memory: DDR-SDRAM DIMM 2 slots (64, 128, 256, 512 MB), 1 slot empty
CompactFlash* card: 1 slot, formats, fonts and macro storage

HD-5 Hard disk: 40 GB, storage of data, formats, fonts etc. eMPS, booklet printing

MM-13-32: Image memory (28 MB)

Security

Data security kit (D)

Optional interface for print functions IB-23 Network card: 10Base-T/100Base-TX SB-70 Network card: Wireless LAN – IEEE 802.11b SB-110FX Network card: 10Base-T/100Base-TX/100Base-FX, FibreOptic

SB-110 Network card: 10-Base-T/100Base-TX
IB-11 Serial interface: RS-232C serial interface (max. 115.2 kbps)

Others

Platen cover (D)

CB-700 Cabinet: Wooden desk with storage capacity
CB-710 Cabinet: Metal desk with storage capacity

TK-825Y Toner kit: Microfine toner vellow for 7.000 pages at 5% A4 coverage **TK-825M Toner kit:** Microfine toner magenta for 7,000

pages at 5% A4 coverage

TK-825C Toner kit: Microfine toner cyan for 7,000 pages at coverage

TK-825K Toner kit: Microfine toner black for 15.000 pages





Select your options to suit your needs:

Document processor



Paper feeder (PF-750)

KYOCERA MITA Europe B.V., Hoeksteen 40, 2132 MS Hoofddorp, The Netherlands, Tel +31 (0) 20 65 40 000, Fax +31 (0) 20 65 31 256,

www.kyoceramita-europe.com, info@kyoceramita-europe.com KYOCERA MITA Corporation, 2-28, 1-Chome, Tamatsukuri, Chuo-Ku, Osaka 540-8585, Japan, www.kyoceramita.com

KM-C2525E - English - 870MT8DSE2525.

Kyocera does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.



